

角目タイプ [JIS G3552 SWM-P]

JIS規格 標準規格品 幅/Width 1m×2m

線径 Wire Diameter mm	空間目 Aperture Width mm	芯々目 Pich mm	開口率 Opening mm	重量 Weight kg/枚	幅 Width mm	幅 Width mm	目数		突出	
							1m側	2m側	1m側	2m側
6	194	200	94.10%	4.44	1000	2000	4	9	100mm	100mm
3.2	146.8	150	95.80%	1.74	1000	2000	6	13	50mm	25mm
4	146	150	94.70%	2.72	1000	2000	6	13	50mm	25mm
5	145	150	93.40%	4.32	1000	2000	6	13	50mm	25mm
5.5	144.5	150	92.80%	5.22	1000	2000	6	13	50mm	25mm
6	144	150	92.20%	6.1	1000	2000	6	13	50mm	25mm
2.6	97.4	100	94.90%	1.74	1000	2000	9	19	50mm	50mm
3.2	96.8	100	93.70%	2.52	1000	2000	9	19	50mm	50mm
4	96	100	92.20%	3.94	1000	2000	9	19	50mm	50mm
5	95	100	90.30%	6.16	1000	2000	9	19	50mm	50mm
6	94	100	88.40%	8.88	1000	2000	9	19	50mm	50mm
3.2	71.8	75	91.60%	3.4	1000	2000	13	26	12.5mm	25mm
6	69	75	84.60%	11.6	1000	2000	12	25	50mm	62.5mm
2.6	47.4	50	89.90%	3.34	1000	2000	19	39	25mm	25mm
3.2	46.8	50	87.60%	5.04	1000	2000	19	39	25mm	25mm
3.2	46.8	50	87.60%	7.86	1300	2400	19	39	25mm	25mm
4	46	50	84.60%	7.9	1000	2000	19	39	25mm	25mm
5	45	50	81.00%	12.3	1000	2000	19	39	25mm	25mm
6	44	50	77.40%	17.7	1000	2000	19	39	25mm	25mm
3.2	26.8	30	79.80%	8	1000	2000	32	65	20mm	25mm

長目タイプ [JIS G3552 SWM-P]

JIS規格 標準品 幅/Width 2m×2m

線径 Wire Diameter mm	空間目 Aperture Width		芯々目 Pich		開口率 Opening mm	重量 Weight kg/枚	幅 Width mm	幅 Width mm	目数		突出 1m側
	縦 mm	横 mm	縦 mm	横 mm					1m側	2m側	
4	46	96	50	100	88.3%	12	2000	2000	39	19	25mm