

角目タイプ [JIS G3552 SWM-P]

JIS規格 標準規格品 幅/Width 1m×2m

その他の規格については特注品となります。

線径 Wire Diameter mm	空間目 Aperture Width mm	芯々目 Pitch mm	開口率 Opening mm	重量 Weight kg/枚	幅 Width mm	幅 Width mm	目数 1m側	目数 2m側	突出 1m側	突出 2m側
3.2	146.8	150	95.8%	1.74	1000	2000	6	13	50mm	25mm
5	145	150	93.4%	4.6	1000	2000	6	13	50mm	25mm
6	144	150	92.2%	6.4	1000	2000	6	13	50mm	25mm
2.6	97.4	100	94.9%	1.74	1000	2000	9	19	50mm	50mm
3.2	96.8	100	93.7%	2.52	1000	2000	9	19	50mm	50mm
4	96	100	92.2%	3.94	1000	2000	9	19	50mm	50mm
5	95	100	90.3%	6.16	1000	2000	9	19	50mm	50mm
6	94	100	88.4%	8.88	1000	2000	9	19	50mm	50mm
2.6	72.4	75	93.2%	2.31	1000	2000	13	26	12.5mm	25mm
3.2	71.8	75	91.6%	3.4	1000	2000	13	26	12.5mm	25mm
2.6	47.4	50	89.9%	3.34	1000	2000	19	39	25mm	25mm
3.2	46.8	50	87.6%	5.04	1000	2000	19	39	25mm	25mm
4	46	50	84.6%	7.9	1000	2000	19	39	25mm	25mm
5	45	50	81.0%	12.3	1000	2000	19	39	25mm	25mm
6	44	50	77.4%	17.7	1000	2000	19	39	25mm	25mm
3.2	26.8	30	79.8%	8	1000	2000	32	65	20mm	25mm

長目タイプ [JIS G3552 SWM-P]

JIS規格 標準品 幅/Width 2m×2m

その他の規格については特注品となります。

線径 Wire Diameter mm	空間目 Aperture Width		芯々目 Pitch		開口率 Opening mm	重量 Weight kg/枚	幅 Width mm	幅 Width mm	目数 1m側	目数 2m側	突出 1m側
	縦 mm	横 mm	縦 mm	横 mm							
4	46	96	50	100	88.3%	12	2000	2000	39	19	25mm